



# METROTRAK

The Powerscreen® Metrotrak is a compact, high performing mobile jaw crushing plant featuring an impressive 900mm x 600mm (35" x 23") single toggle jaw crusher. With an aggressive crushing action and a high output even at tight settings, the Metrotrak is ideally suited for operators on the mining, quarrying and recycling industries, especially those working in urban locations or where space is restricted.



## ✓ APPLICATIONS

### AGGREGATE



Sand & gravel  
Blasted rock  
River rock

### RECYCLING



C&D waste  
Overburden  
Foundry waste

### MINING



Processed ores  
Processed minerals

## TECHNICAL HIGHLIGHTS



### INCREASED PRODUCTIVITY

- Superior tunnelling reduces the risk of rebar snagging giving excellent machine uptime.
- Enhanced material flow via new design bypass chute and product conveyor.
- Jaw level sensor option promotes material flow by optimising feeder speeds, increasing daily productivity.
- Powerscreen Pulse intelligent monitoring as standard.



### VERSATILITY

- Ideal for C&D waste / recycling applications with hydraulic deflector plate and hydraulically raise / lower product conveyor options.
- Jaw unblock option combines the benefits of hydrostatic drive with the fuel efficiency of direct drive.



### SERVICEABILITY

- Centralised low level hydraulics and electrics.



# TECHNICAL SPECIFICATION



## 1 HOPPER

Wear resistant feed hopper  
Length: 4m (13'1")  
Width: 1.8m (5'9")  
Capacity: 3.6m<sup>3</sup> (4.7yds<sup>3</sup>)

## 2 CRUSHER

High capacity single toggle jaw  
Chamber size: 900mm x 600mm  
(35" x 23")  
Min CSS: 40mm (1.5")\*  
Max CSS: 100mm (4")\*

## 3 PRODUCT CONVEYOR

Width: 800mm (32")  
Discharge height: 2.9m (9'6")

## 4 BYPASS CONVEYOR (OPTION)

Width: 600mm (23.6")  
Discharge height: 2m (6'7")

## 5 FEEDER

Vibrating pan feeder  
Length: 3.8m (12'5")  
Width: 800mm (2'7")

## 6 TRACKS

Width: 400mm (15.7")

## 7 POWER UNIT

Tier 3/Stage 3A: John Deere 4045  
126kW (169hp)  
Tier 4F/Stage 4: CAT C4.4 129kW  
(173hp)  
Fuel tank capacity: 400 L (106 US  
GAL)



# DIMENSIONS



## GET IN TOUCH

### Dungannon

200 Coalisland Road, Dungannon,  
Co Tyrone, BT71 4DR, Northern Ireland  
Tel: +44 (0) 28 87 718 500  
Fax: +44 (0) 28 87 747 231

### Louisville

11001 Electron Drive,  
Louisville, Kentucky, 40299 USA  
Tel: +1 502 736 5200  
Fax: +1 502 736 5202



[www.powerscreen.com](http://www.powerscreen.com)

The material in this document is for information only and is subject to change without notice. Powerscreen assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples provided by Dealers. These results will vary depending on crusher chamber settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only, some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. All machines are CE Approved.

Powerscreen® is a registered trademark of Terex GB Limited in the United States of America and many other countries. Copyright 2019 Terex GB Limited. Published and Printed in April 2019.