/ SHREDDING

Komptech Crambo


DUAL-SHAFT, HIGH-TORQUE
ORGANICS AND WOOD WASTE SHREDDER



Sold and Serviced in B.C. by



1-888-852-9021













A powerful CAT® engine, 134 teeth, and counterrotating drums devour even the toughest wood and green waste materials.

/ QUICK STATS

- Make short work of green waste, wood waste, stumps, spools, and land clearing debris
- Work quickly feeding directly into an 11-foot hopper opening
- Easily swap screen baskets for variable output between 2-inch and 24-inch minus particle sizes





KOMPTECH CRAMBO / Technical Specifications

Machine Model	CRAMBO 6000	CRAMBO 3400
Power		
Diesel Engine / Horsepower:	CAT® C18 Tier 4 Final / 600 HP	CAT° C9 Tier 4 Final / 330 HP
Drive:	Hydraulic Drum Drive - Single Side	Hydraulic Drum Drive - Both Sides
Proportion		
Transport Dimensions (LxWxH):	22'9" x 9'4" x 10'9" (6.9 x 2.9 x 3.3 m)	22'9" x 9'4" x 10'9" (6.9 x 2.9 x 3.3 m)
Working Dimensions (LxWxH):	37'3" x 10'10" x 13'7" (11.4 x 3.3 x 4.1 m)	37'3" x 10'10" x 13'7" (11.4 x 3.3 x 4.1 m)
Drum Diameter / Drum Length:	2'(610 mm)/9'3"(2.8 m)	2'(610 mm)/9'3"(2.8 m)
Loading Height:	9'6" (2.9 m)	9'6" (2.9 m)
Discharge Height:	6'-13'7" (1.8-4.2 m)	6'-13'7" (1.8-4.2 m)
Weight:	~50,000 lbs	~48,800 lbs
Performance (dependent on material)		
Maximum Drum Speed:	38 rpm	29 rpm
Maximum Throughput:	~100 tons/hr	~50 tons/hr

Think Viably for industry expertise, world-class products, parts, service, and support.

Wherever you work.



CONSTRUCTION AND DEMOLITION (C&D)



MUNICIPAL SOLID WASTE (MSW)



ORGANICS WASTE



SINGLE-STREAM RECYCLING



Scan to see the Crambo in action

